**iCAST Series** 

# **HAVE** A SMART BLAST!

THE ONLY INTELLIGENT MARKETING & ADVERTISING MATERIAL PLATFORM HAND DRYER WITH WIFI. GSM & LAN TECHNOLOGY IN THE INDUSTRY

#### **FEATURES**

- Vandal proof-not scratchable with any sharp object
- Fastest drying time on the market
- Automatic infrared actuated sensor, for power conservation and maximum hygiene
- Exclusive: Adjustable output airflow temperature
- Robust, vandal proof, tamper-proof design and construction for greater product durability and longevity
- lifetime warranty the best one in the industry
- High velocity (100 CFM) airflow for ultra high speed hand drying: 8 sec.
- 5.5 inches touch screen, full WiFi, GSM, Ethernet, Bluetooth connectivity for data upload & remote dryer maintenance
- Unique interactive communication between the machine and the end user, full WiFi monitoring worldwide
- Radio FM/AM worldwide (option)
- · Smallest footprint on the market
- Universal voltage: automatic voltage switching for ease of installation
- Designed for easy installation
- Contributes to LEED and BOMA building certifications
- Vandal proof ABS plexiglass screen protector
- Tamperproof screws
- Fire Alarm and Active Shooter Alarm (optional)














## **APPLICATIONS**

- All public and commercial bathrooms and clean up areas. Factories, restaurants, pools, gyms, hospitals and schools
- All facilities with a need for advertising
- · Marketing and advertising companies for better reach of target audiences
- Great platform to reach employees and staff internally
- Made for high traffic public areas

























**Voltage** Universal 115–230\*VAC (\*50/60Hz) **Wattage** 1450 W at 5.2A (230VAC)

**Motor** Vacuum Motor, 36,000 RPM (outside the enclosure) 5/8HP 20,000 RPM (installed in the enclosure)

**Colour** White, Black and Stainless Steel **Finish** Chrome, scratch-resistant porcelain, brushed stainless steel.

**Heating Element** 725w resistance coil. **Construction Material** Reinforced Steel

**Controls & Wiring** Automatic resetting thermostat with cutout when airflow is restricted. Infrared sensor cutout two seconds after hand removal, and 85 seconds after initiating drying.

**Installation** Removable predrilled baseplate for easy mounting.

#### Warranty LIFETIME

CSA certified for use in Canada and the U.S. CE approved for use where applicable.

**Patent Pending** 

### **ORDERING GUIDE**

Model No.	Color	Watts cold air hot air	Volts Hz	Air Velocity LFM	Air Volume CFM	Noise dB	Dimensions (W x H x D) (mm/in.)	Weight (kg/lbs.)
c-40000000	White	725-1450	115-230,50-60	19,000	100	78	235 x 280 x 170 ( 9.25 x 11.02 x 6.69 )	5/11
C-40000002	Black	725-1450	115-230, 50-60	19,000	100	78	235 x 280 x 170 ( 9.25 x 11.02 x 6.69 )	5/11
C-400220000	Brushed stainless steel	725-1450	115-230, 50-60	19,000	100	78	235 x 280 x 170 ( 9.25 x 11.02 x 6.69 )	5/11
C-400230000	Chrome	725-1450	115-230, 50-60	19,000	100	78	235 x 280 x 170 ( 9.25 x 11.02 x 6.69 )	5/11



















